

View Online at <https://aerobasegroup.com/nsn/5320-00-929-9194>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.760 inches and 1.785 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.2884 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

0.439 inches

**Grip Length:**

Between 1.427 inches and 1.442 inches

**Thread Size:**

0.250 inches

**Countersink Angle:**

100.0 degrees

**Special Features:**

0.2615 in. Second shank dia, and lubrication cetyl alcohol

**Material:**

Steel comp 8740 or steel comp 4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.