## NSN 5320-00-931-3033

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-931-3033 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.183 inches and 2.208 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3547 inches **Head Major Diameter:** 0.522 inches Tip Diameter: 0.3202 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.802 inches and 1.817 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-00-931-3033

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.