NSN 5320-00-931-3040



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-931-3040 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.750 inches and 1.775 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.4053 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.598 inches Tip Diameter: 0.3815 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.312 inches and 1.317 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 108000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium or cadmium and chromate or cadmium and phosphate **Surface Treatment Specification:** Qq-p-416 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1724 professional/industrial association standard

NSN 5320-00-931-3040

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0