## NSN 5320-00-931-3060



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-00-931-3060 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.072 inches and 1.097 inches **Head Style:** Err-090 **Head Height:** Between 0.058 inches and 0.070 inches **Shank Diameter:** 0.2766 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.392 inches and 0.403 inches Tip Diameter: 0.2629 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.740 inches and 0.755 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp 4340 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas1728 professional/industrial association standard

### Shelf Life:

N/a

# NSN 5320-00-931-3060

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0