## NSN 5320-00-931-3063

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-931-3063 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.260 inches and 1.285 inches **Head Style:** Err-090 **Head Height:** Between 0.058 inches and 0.070 inches Shank Style: Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.392 inches and 0.403 inches **Tip Diameter:** 0.2590 inches Lubrication: Cetyl alcohol **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1728 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-00-931-3063

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.