

View Online at <https://aerobasegroup.com/nsn/5320-00-931-3066>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.760 inches and 0.785 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.058 inches and 0.070 inches

**Shank Diameter:**

0.264 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

Between 0.379 inches and 0.389 inches

**Tip Diameter:**

0.2564 inches

**Lubrication:**

Cetyl alcohol

**End Application:**

W/s: aircraft, galaxy c-5; aircraft (ac-130h, mc-130h, ec-130e, hc-130); aircraft, starlifter c-141; aircraft, hercules c-130; f117a aircraft

**Grip Length:**

Between 0.427 inches and 0.442 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

108000 single pounds per square inch

**Material:**

Steel comp 8740 or steel comp e4340

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1728 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-s-6049 spec.