NSN 5320-00-931-3069

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-931-3069 **Thread Class:** Aal **Thread Direction:** Right-hand Fastener Length: Between 1.5720 inches and 1.5970 inches **Head Style:** Err-090 **Head Height:** Between 0.0580 inches and 0.0700 inches **Shank Diameter:** 0.2766 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** Between 0.3790 inches and 0.3890 inches Tip Diameter: 0.2525 inches Lubrication: Cetyl alcohol **Grip Length:** Between 1.2400 inches and 1.2550 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Thread Size:** 0.2500 inches **Shear Strength:** 108000 single pounds per square inch Material: Steel comp 8740 or steel comp e4340 **Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-00-931-3069

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.