# NSN 5320-00-931-3109

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-931-3109



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.333 inches and 2.358 inches

#### Head Style:

Err-090

# **Head Height:**

Between 0.092 inches and 0.094 inches

#### Shank Diameter:

0.4224 inches

#### Shank Style:

Pin-rivet, tapered, threaded

#### Head Major Diameter:

Between 0.605 inches and 0.619 inches

#### Tip Diameter:

0.3841 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

Between 1.927 inches and 1.942 inches

# Thready Qty Per Inch (tpi):

24

# **Thread Size:**

0.375 inches

# Material:

Steel comp 8740 or steel comp e4340

# Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

#### Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-00-931-3109

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

Mil-std (military Standard):

Mil-s-6049 spec.

