

View Online at <https://aerobasegroup.com/nsn/5320-00-931-3110>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.896 inches and 1.921 inches

Head Style:

Flush countersunk

Shank Diameter:

0.4053 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.598 inches

Tip Diameter:

0.3776 inches

End Application:

W/s: aircraft, phantom f-4; aircraft, starlifter c-141; f4s aircraft

Grip Length:

1.505 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Thread Size:

0.3750 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8740 or steel comp 4340

Material Specification:

Mil-s-6049 military specification 1st material response or mil-s-5000 military specification 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.