# NSN 5320-00-932-3986

Pin-rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-932-3986

## Head Style:

Flush countersunk

## Shank Diameter:

Between 0.1535 inches and 0.1560 inches

## Shank Style:

Err-090

#### Head Major Diameter:

0.220 inches

## Grip Length:

Between 0.751 inches and 0.812 inches

## **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp 4340 or steel comp 4037 or steel comp 4130 or steel comp 4340

## **Material Specification:**

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or ams 6415 assn standard 5th material response or ams 6300 assn standard 6th material response or mil-s-6758 military specification 7th material response or mil-s-5000 military specification 8th material response

## Surface Treatment:

Cadmium

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## **Specification Data:**

80205-nas1055 professional/industrial association standard

## Shelf Life:

N/a

Unit Of Measure:

```
---
```

## Demilitarization:

No

Fiig:

A528u0

## Mil-std (military Standard):

Mil-s-6098 spec.