

View Online at <https://aerobasegroup.com/nsn/5320-00-932-3987>

Head Style:

Flush countersunk

Shank Diameter:

Between 0.1535 inches and 0.1560 inches

Shank Style:

Err-090

Head Major Diameter:

0.220 inches

Grip Length:

Between 0.626 inches and 0.688 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 8735 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp 4340 or steel comp 4037 or steel comp 4130 or steel comp 4340

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-5626 military specification 4th material response or ams 6415 assn standard 5th material response or ams 6300 assn standard 6th material response or mil-s-6758 military specification 7th material response or mil-s-5000 military specification 8th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Specification Data:

80205-nas1055 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.