

View Online at <https://aerobasegroup.com/nsn/5320-00-932-3991>

Head Style:

Flush countersunk

Shank Diameter:

Between 0.1535 inches and 0.1560 inches

Shank Style:

Err-090

Head Major Diameter:

Between 0.2203 inches and 0.2575 inches

Grip Length:

Between 0.876 inches and 0.938 inches

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

100.0 degrees

Material:

Steel comp 8735 or steel comp 8740 or steel comp 8740 or steel comp 6150 or steel comp 4140 or steel comp e4340 or steel comp 4340 or steel comp 4130

Material Specification:

Mil-s-6098 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 3rd material response or mil-s-8503 military specification 4th material response or mil-s-5626 military specification 5th material response or mil-s-5000 military specification 6th material response or mil-s-5000 military specification 7th material response or ams 6415 assn standard 7th material response or mil-s-6758 military specification 8th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Specification Data:

80205-nas1055 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0

Mil-std (military Standard):

Mil-s-6098 spec.