NSN 5320-00-935-9065

Blind Rivet - Page 1 of 1



view Online at https://aerobasegroup.com/hsn/5520-00-955-9065
Fastener Length:
Between 0.241 inches and 0.271 inches
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.163 inches and 0.165 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
Between 0.296 inches and 0.332 inches
Expansion Device:
Threaded mandrel
Lubrication:
Paraffin wax or dry film
Grip Length:
Between 0.094 inches and 0.156 inches
Hardness Rating:
30.0 rockwell c and 45.0 rockwell c
Shear Strength:
2700 double pounds per square inch
Countersink Angle:
100.0 degrees
Heat Treatment:
Solution heat treated
Material:
Iron alloy 660
Material Specification:
Ams 5735 assn standard single material response or ams 5736 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A040a0