

View Online at <https://aerobasegroup.com/nsn/5320-00-938-6039>

Fastener Length:

Between 0.778 inches and 0.808 inches

Head Style:

Hexagon

Head Height:

0.096 inches

Shank Diameter:

Between 0.163 inches and 0.165 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.096 inches and 0.657 inches

Width Across Flats:

Between 0.244 inches and 0.250 inches

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Shear Strength:

3355 double pounds per square inch

Material:

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5614 assn standard 2nd material response sleeve or amstm a582 assn standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve and passivate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification single treatment response bolt

Specification Data:

80205-nas1669 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.