

View Online at <https://aerobasegroup.com/nsn/5320-00-938-6039>

**Fastener Length:**

Between 0.778 inches and 0.808 inches

**Head Style:**

Hexagon

**Head Height:**

0.096 inches

**Shank Diameter:**

Between 0.163 inches and 0.165 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.096 inches and 0.657 inches

**Width Across Flats:**

Between 0.244 inches and 0.250 inches

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Shear Strength:**

3355 double pounds per square inch

**Material:**

Steel comp 304 sleeve or steel comp 303f sleeve or steel comp 303 sleeve

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 1st material response sleeve or ams 5614 assn standard 2nd material response sleeve or amstm a582 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve and passivate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl2 federal specification single treatment response bolt

**Specification Data:**

80205-nas1669 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.