# NSN 5320-00-944-0002

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-944-0002

## **Thread Class:**

3a

**Thread Direction:** 

Right-hand

# Fastener Length:

Between 1.565 inches and 1.585 inches

## Head Style:

Err-090

### Head Height:

Between 0.055 inches and 0.065 inches

## Width Between Flats:

Between 0.079 inches and 0.081 inches

## Shank Diameter:

Between 0.189 inches and 0.190 inches

### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Grip Length:

1.255 inches

# Thread Size:

0.190 inches

# Heat Treatment:

T-6 solution heat treated

### Material:

Aluminum alloy 7075

# Material Specification:

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

### Surface Treatment:

Anodize

# Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

# **Thread Series Designator:**

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

# NSN 5320-00-944-0002

Pin-rivet - Page 2 of 2

# Mil-std (military Standard):

Mil-a-8625 spec.

