## NSN 5320-00-944-0019

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-944-0019 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color: Bronze Fastener Length:** Between 1.240 inches and 1.260 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.127 inches and 0.130 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style: Head Major Diameter:** Between 0.475 inches and 0.505 inches **Grip Length:** 0.755 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 95000 single pounds per square inch Material: Steel comp 4140 or steel comp 8740 or steel comp 4130 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-00-944-0019

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.