
# NSN 5320-00-945-2569

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

Identification Code Color:

Bronze

#### Fastener Length:

Between 1.740 inches and 1.760 inches

#### Head Style:

Err-090

Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.127 inches and 0.130 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

# Head Major Diameter:

Between 0.475 inches and 0.505 inches

Grip Length:

1.255 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

**Thread Size:** 

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

# Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

# **Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military

specification 3rd material response

#### Surface Treatment:

Cadmium

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

# NSN 5320-00-945-2569

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.

