

View Online at <https://aerobasegroup.com/nsn/5320-00-945-2617>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.678 inches and 0.698 inches

Head Style:

Err-090

Head Height:

Between 0.098 inches and 0.112 inches

Width Between Flats:

Between 0.127 inches and 0.129 inches

Shank Diameter:

Between 0.311 inches and 0.312 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.472 inches and 0.502 inches

Grip Length:

Between 0.183 inches and 0.193 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

14600 double pounds per square inch

Special Features:

HI72 hi-lok collar included with item

Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.