NSN 5320-00-948-7283

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-948-7283 **Fastener Length:** 0.506 inches **Head Style:** Small pan **Head Height:** Between 0.131 inches and 0.141 inches **Shank Diameter:** Between 0.310 inches and 0.312 inches **Shank Style:** Self-plugging mechanically locked stem **Head Major Diameter:** Between 0.480 inches and 0.522 inches **Expansion Device:** Serrated stem-type w **Grip Length:** Between 0.219 inches and 0.282 inches Min. Tensile Strength (psi): 112000 pounds per square inch **Hardness Rating:** 48.0 rockwell c stem and 53.0 rockwell c stem **Shear Strength:** 8500 single pounds per square inch Material: Steel comp 8740 stem **Material Specification:** 66 federal standard 1st material response sleeve or astm a547 assn standard 2nd material response sleeve or 66 military specification 2nd material response sleeve or mil-s-6758 military specification 3rd material response sleeve **Surface Treatment:** Cadmium stem **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Mil-s-6758 spec.

Mil-std (military Standard):

Fiig: A040a0