

View Online at <https://aerobasegroup.com/nsn/5320-00-948-7297>

**Fastener Length:**

1.490 inches

**Head Style:**

Hexagon countersunk

**Head Height:**

Between 0.072 inches and 0.079 inches

**Shank Diameter:**

Between 0.258 inches and 0.260 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Threaded mandrel

**Grip Length:**

Between 0.970 inches and 1.031 inches

**Width Across Flats:**

Between 0.458 inches and 0.472 inches

**Shear Strength:**

5300 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

**Material Specification:**

Qq-s-764 federal specification 1st material response nut or qq-s-763 federal specification 2nd material response nut or ams 5639 assn standard 3rd material response nut or ams 5641 assn standard 4th material response nut

**Surface Treatment:**

Passivate nut and cadmium nut

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Specification Data:**

80205-nas1674 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.