

View Online at <https://aerobasegroup.com/nsn/5320-00-948-7297>

Fastener Length:

1.490 inches

Head Style:

Hexagon countersunk

Head Height:

Between 0.072 inches and 0.079 inches

Shank Diameter:

Between 0.258 inches and 0.260 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Threaded mandrel

Grip Length:

Between 0.970 inches and 1.031 inches

Width Across Flats:

Between 0.458 inches and 0.472 inches

Shear Strength:

5300 double pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Qq-s-764 federal specification 1st material response nut or qq-s-763 federal specification 2nd material response nut or ams 5639 assn standard 3rd material response nut or ams 5641 assn standard 4th material response nut

Surface Treatment:

Passivate nut and cadmium nut

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Specification Data:

80205-nas1674 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.