NSN 5320-00-948-7332

Tubular Rivet - Page 1 of 1

Fiig: A040a0



View Online at https://aerobasegroup.com/nsn/5320-00-948-7332 **Fastener Length:** Between 0.212 inches and 0.226 inches **Head Style:** Oval/truss **Head Height:** Between 0.030 inches and 0.038 inches **Hole Diameter:** Between 0.084 inches and 0.088 inches **Shank Diameter:** Between 0.118 inches and 0.123 inches **Shank Style:** Tubular **Head Major Diameter:** Between 0.213 inches and 0.223 inches **Hole Depth:** Between 0.078 inches and 0.110 inches **Shear Strength:** 32000 double pounds per square inch Material: Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Specification Or Standard:** 12 type and 3 class and e grade Shelf Life: N/a **Unit Of Measure: Demilitarization:** No