

View Online at <https://aerobasegroup.com/nsn/5320-00-948-7348>

Fastener Length:

Between 0.403 inches and 0.433 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.164 inches and 0.165 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.325 inches and 0.332 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Grease film

Grip Length:

Between 0.282 inches and 0.344 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 46.0 rockwell c

Shear Strength:

3760 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Heat Treatment:

Annealed

Material:

Steel comp 8740 stem

Material Specification:

Mil-s-6049 military specification single material response stem

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416 type 1 class 3 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-s-6049 spec.