

View Online at <https://aerobasegroup.com/nsn/5320-00-948-7348>

**Fastener Length:**

Between 0.403 inches and 0.433 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.164 inches and 0.165 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.325 inches and 0.332 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Grease film

**Grip Length:**

Between 0.282 inches and 0.344 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 46.0 rockwell c

**Shear Strength:**

3760 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Heat Treatment:**

Annealed

**Material:**

Steel comp 8740 stem

**Material Specification:**

Mil-s-6049 military specification single material response stem

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416 type 1 class 3 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6049 spec.