

View Online at <https://aerobasegroup.com/nsn/5320-00-951-0268>

Fastener Length:

0.467 inches

Head Style:

Small pan

Head Height:

Between 0.062 inches and 0.070 inches

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.250 inches and 0.272 inches

Expansion Device:

Serrated stem-type w

Grip Length:

Between 0.281 inches and 0.345 inches

Min. Tensile Strength (psi):

112000 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

2340 single pounds per square inch

Material:

Steel comp 8740 stem

Material Specification:

66 federal standard 1st material response sleeve or astm a547 assn standard 2nd material response sleeve or 66 federal standard 3rd material response sleeve or mil-s-6758 military specification 3rd material response sleeve

Surface Treatment:

Cadmium stem

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.