

View Online at <https://aerobasegroup.com/nsn/5320-00-952-4161>

Fastener Length:

Between 0.565 inches and 0.595 inches

Head Style:

Universal

Head Height:

Between 0.056 inches and 0.076 inches

Shank Diameter:

Between 0.186 inches and 0.190 inches

Shank Style:

Self-plugging

Head Major Diameter:

Between 0.356 inches and 0.394 inches

Expansion Device:

Mandrel-type c

Grip Length:

Between 0.251 inches and 0.375 inches

Shear Strength:

460 double pounds per square inch

Material:

Steel comp 1025 mandrel or steel comp 1045 mandrel or steel comp 1012 mandrel or steel comp 1012 mandrel or steel comp 1075 mandrel or steel comp 1025 mandrel

Material Specification:

Qq-a-430 federal specification single material response body

Surface Treatment:

Zinc mandrel or chromate mandrel or cadmium mandrel and chromate mandrel or cadmium mandrel and phosphate mandrel or phosphate zinc mandrel and phosphate zinc mandrel

Surface Treatment Specification:

Qq-z-325, type 2, cl 2 federal specification 1st treatment response mandrel or qq-p-416 assn standard 2nd treatment response mandrel or mil-p-16232, ty z, cl 2 military specification 3rd treatment response mandrel or mil-p-16232, ty z, cl 4b military specification 4th treatment response mandrel

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.