## NSN 5320-00-954-8496

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-954-8496

Fastene	r I er	ath:
газіспе	LEI	ıuıı.

Between 0.490 inches and 0.510 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.155 inches and 0.159 inches

**Shank Style:** 

Self-plugging mechanically locked stem

**Head Major Diameter:** 

Between 0.282 inches and 0.290 inches

**Expansion Device:** 

Serrated stem-type w

**Grip Length:** 

Between 0.313 inches and 0.375 inches

**Shear Strength:** 

1090 single pounds per square inch

**Countersink Angle:** 

Between 98.5 degrees and 101.5 degrees

Material:

Nickel alloy 400 stem

**Material Specification:** 

Qq-n-281 federal specification single material response stem

**Surface Treatment:** 

Cadmium stem and chromate stem

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl @2 federal specification all treatment responses sleeve

**Specification Data:** 

80205-nas1399 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0