

View Online at <https://aerobasegroup.com/nsn/5320-00-957-1430>

**Fastener Length:**

0.295 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Pull through hollow shank

**Head Major Diameter:**

0.225 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Shear Strength:**

125 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 1006 stem or steel comp 1008 stem or steel comp 1010 stem or steel comp 1012 stem or steel comp 1015 stem or steel comp 1016 stem or steel comp 1018 stem or steel comp 1019 stem or steel comp 1021 stem or steel comp 1022 stem or steel comp 1026 stem or steel comp 1030 stem or steel comp 1035 stem or steel comp 1038 stem or steel comp 1524 stem or steel comp 1541 stem

**Material Specification:**

Mil-w-7986 military specification single material response sleeve

**Surface Treatment:**

Anodize sleeve or chromate sleeve

**Surface Treatment Specification:**

Mil-a-8625 type 1 cl 1 military specification 1st treatment response sleeve or mil-c-5541 cl 1a military specification 2nd treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-w-7986 spec.