

View Online at <https://aerobasegroup.com/nsn/5320-00-957-7782>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

0.895 inches

Head Style:

Flush countersunk

Width Between Flats:

0.2538 inches

Shank Diameter:

0.2624 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.413 inches

End Application:

W/s: aircraft, f-16; aircraft, hercules c-130, c-130f, kc-130; aircraft, stratolifter c-135; aircraft, galaxy c-5; aircraft, hx unique; aircraft, starlifter c-141; aircraft, phantom f-4

Grip Length:

0.562 inches

Thread Size:

0.250 inches

Countersink Angle:

100.0 degrees

Special Features:

0.2538 in. Second shank dia, and lubrication cetyl alcohol

Material:

Steel comp 8740

Material Specification:

Mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1724 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-6049 spec.