## NSN 5320-00-958-6194

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-958-6194

Fas	ten	er	م ا	กด	ıth	
газ	LEI	ıeı	ᆫ	ιıu	ıuı	١.

Between 0.365 inches and 0.385 inches

**Head Style:** 

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:** 

Between 0.139 inches and 0.143 inches

**Shank Style:** 

Self-plugging mechanically locked stem

**Head Major Diameter:** 

Between 0.221 inches and 0.229 inches

**Expansion Device:** 

Serrated stem-type w

**Grip Length:** 

Between 0.188 inches and 0.250 inches

**Shear Strength:** 

619 single pounds per square inch

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp e4340 stem or steel comp 4340 stem or steel comp 8740 stem

**Material Specification:** 

Qq-n-281 federal specification all material responses locking ring

Surface Treatment:

Cadmium stem and chromate stem

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response stem

**Specification Data:** 

80205-nas1739 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5000 spec.