NSN 5320-00-959-0139

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-959-0139

Fastener Length:
Between 0.212 inches and 0.226 inches
Head Style:
Oval/truss
Head Height:
Between 0.020 inches and 0.026 inches
Hole Diameter:
Between 0.062 inches and 0.066 inches
Shank Diameter:
Between 0.085 inches and 0.089 inches
Shank Style:
Tubular
Head Major Diameter:
Between 0.142 inches and 0.152 inches
Hole Depth:
Between 0.047 inches and 0.078 inches
Shear Strength:
32000 double pounds per square inch
Material:
Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012
or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp
1020 or steel comp 1021 or steel comp 1022
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Specification Or Standard:
12 type and 3 class and e grade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0