## NSN 5320-00-959-0334

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-959-0334

Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Bronze
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Height:
Between 0.037 inches and 0.047 inches
Width Between Flats:
Between 0.0791 inches and 0.0801 inches
Shank Diameter:
Between 0.1625 inches and 0.1635 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.242 inches and 0.262 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
0.193 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.164 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color bronze
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Thread Series Designator:
Unjc
Shelf Life:
N/a

## NSN 5320-00-959-0334

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

