

View Online at <https://aerobasegroup.com/nsn/5320-00-959-7214>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.503 inches and 0.523 inches

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.079 inches and 0.080 inches

Shank Diameter:

Between 0.189 inches and 0.190 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

End Application:

Engine, aircraft tf33-pw-102 (c-135e, ec-135h/k/p); engine, aircraft, j-57 all models (c-135, ec-135, b-52); aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130); helicopter, search and rescue, hh-60h; engine, aircraft tf33-p-3/5/9 (c/ec-135, b-52h); aircraft, c-2a (reprocured); helicopter, mh-53e; engine, aircraft, tf-33-p-7 (c-141a/b); helicopter, carrier based asw, sh-60f.

Grip Length:

0.193 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.