

View Online at <https://aerobasegroup.com/nsn/5320-00-959-7303>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.127 inches and 1.147 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

End Application:

W/s: aircraft, starlifter c-141; aircraft, hx unique; helicopter, hx unique; fms-a7 aircraft; joint stars target radar system; aircraft, f-111; aircraft, galaxy c-5; aircraft, stratolifter c-135; aircraft, c-2a (reprocured); engine, aircraft, t56-a-7/15 (c-130b/e/h/n/p)

Grip Length:

Between 0.807 inches and 0.817 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160 pounds per square inch

Thread Size:

0.190 inches

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6758 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.