

View Online at <https://aerobasegroup.com/nsn/5320-00-962-5796>

Fastener Length:

Between 0.290 inches and 0.320 inches

Head Style:

Hexagon countersunk

Head Height:

Between 0.067 inches and 0.074 inches

Shank Diameter:

Between 0.178 inches and 0.180 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film and wax

Grip Length:

Between 0.094 inches and 0.156 inches

Width Across Flats:

Between 0.277 inches and 0.283 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Shear Strength:

1920 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Bolt color green

Heat Treatment:

Annealed

Material:

Steel comp 303 sleeve or steel comp 304 sleeve or steel comp 303f sleeve

Material Specification:

Qq-a-225/9 federal specification single material response bolt

Surface Treatment:

Passivate sleeve and cadmium sleeve or cadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Specification Data:

80205-nas1754 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A040a0

Mil-std (military Standard):

Mil-a-8625 spec.