

View Online at <https://aerobasegroup.com/nsn/5320-00-962-5814>

**Fastener Length:**

Between 0.415 inches and 0.445 inches

**Head Style:**

Hexagon countersunk

**Head Height:**

Between 0.067 inches and 0.074 inches

**Shank Diameter:**

Between 0.178 inches and 0.180 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film and wax

**Grip Length:**

Between 0.219 inches and 0.281 inches

**Width Across Flats:**

Between 0.277 inches and 0.283 inches

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Shear Strength:**

1920 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Bolt color green

**Heat Treatment:**

Annealed

**Material:**

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

**Material Specification:**

Qq-a-225/9 federal specification single material response bolt

**Surface Treatment:**

Passivate sleeve and cadmium sleeve or cadmium sleeve and chromate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

**Specification Data:**

80205-nas1754 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.