NSN 5320-00-962-5826

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-962-5826

Fastener Length:

Between 0.293 inches and 0.323 inches

Head Style:

Hexagon countersunk

Head Height:

Between 0.072 inches and 0.079 inches

Shank Diameter:

Between 0.213 inches and 0.215 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film and wax

Grip Length:

Between 0.156 inches and 0.219 inches

Width Across Flats:

Between 0.332 inches and 0.346 inches

Min. Tensile Strength (psi):

180000 pounds per square inch

Shear Strength:

3100 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Bolt color green

Heat Treatment:

Annealed

Material:

Steel comp 4140 nut or steel comp 8740 nut or steel comp 4130 nut

Material Specification:

Qq-a-282 federal specification single material response bolt

Surface Treatment:

Passivate sleeve and cadmium sleeve or cadmium sleeve and chromate sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Specification Data:

80205-nas1754 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5320-00-962-5826

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.

