NSN 5320-00-969-4531

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-969-4531

Thread Class: 3a **Thread Direction: Right-hand Identification Code Color:** Bronze **Fastener Length:** Between 1.035 inches and 1.055 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches Shank Diameter: Between 0.3735 inches and 0.3745 inches Shank Style: Head Major Diameter: Between 0.565 inches and 0.600 inches Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.505 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Color bronze

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military

specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response



NSN 5320-00-969-4531

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

