

View Online at <https://aerobasegroup.com/nsn/5320-00-971-0411>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.197 inches and 0.199 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.329 inches and 0.388 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Grease film

**Grip Length:**

Between 0.469 inches and 0.531 inches

**Hardness Rating:**

39.0 rockwell c nut and 43.0 rockwell c nut

**Shear Strength:**

5240 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

**Material Specification:**

Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut

**Surface Treatment:**

Passivate sleeve and cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.