NSN 5320-00-971-8138

Tubular Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-00-971-8138

Fastener Length:
Between 0.554 inches and 0.570 inches
Head Style:
Oval/truss
Head Height:
Between 0.030 inches and 0.038 inches
Hole Diameter:
Between 0.084 inches and 0.088 inches
Shank Diameter:
Between 0.118 inches and 0.123 inches
Shank Style:
Tubular
Head Major Diameter:
Between 0.213 inches and 0.223 inches
Hole Depth:
Between 0.078 inches and 0.110 inches
Shear Strength:
32000 double pounds per square inch
Material:
Steel comp 1005 or steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012
or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp
1020 or steel comp 1021 or steel comp 1022
Material Specification:
66 federal standard all material responses
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Specification Or Standard:
12 type and 3 class and e grade
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A040a0