## NSN 5320-00-972-3327

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-972-3327 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.865 inches and 0.885 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.311 inches and 0.312 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol **Grip Length:** 0.380 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response or ams 5628 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-00-972-3327

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.