# NSN 5320-00-972-3328

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-972-3328



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 0.990 inches and 1.010 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.068 inches and 0.078 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.311 inches and 0.312 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.475 inches and 0.505 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

0.505 inches

## Thready Qty Per Inch (tpi):

24

## Thread Size:

0.312 inches

## Shear Strength:

125000 single pounds per square inch

# Material:

Steel comp 431

# Material Specification:

Mil-s-18732 military specification single material response or ams 5628 assn standard single material response

## Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# Thread Series Designator:

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-00-972-3328

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

