# NSN 5320-00-972-3330

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-972-3330



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 0.997 inches and 1.017 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.078 inches and 0.088 inches

### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

### Lubrication:

Cetyl alcohol

## Grip Length:

0.567 inches

## Thready Qty Per Inch (tpi):

24

### Thread Size:

0.375 inches

## Shear Strength:

125000 single pounds per square inch

### Material:

Steel comp 431

### **Material Specification:**

Mil-s-18732 military specification single material response or ams 5628 assn standard single material response

### Surface Treatment:

Cadmium and chromate

### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-00-972-3330

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

