
# NSN 5320-00-972-3332

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.597 inches and 1.617 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.078 inches and 0.088 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.565 inches and 0.600 inches

#### Lubrication:

Cetyl alcohol

# Grip Length:

1.067 inches

### Thready Qty Per Inch (tpi):

24

#### Thread Size:

0.375 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp 431

#### **Material Specification:**

Mil-s-18732 military specification single material response or ams 5628 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

#### Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--



# NSN 5320-00-972-3332

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.

