## NSN 5320-00-972-3349

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-972-3349 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.253 inches and 1.273 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.081 inches **Shank Diameter:** Between 0.189 inches and 0.190 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.349 inches and 0.354 inches **Grip Length:** 0.943 inches **Thread Size:** 0.190 inches **Countersink Angle:** 100.0 degrees **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A528u0

## NSN 5320-00-972-3349

Pin-rivet - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.