## NSN 5320-00-972-3359

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-00-972-3359

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Fastener Length:

Between 1.503 inches and 1.523 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.055 inches and 0.065 inches

#### Width Between Flats:

Between 0.079 inches and 0.081 inches

#### Shank Diameter:

Between 0.189 inches and 0.190 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

#### Grip Length:

1.193 inches

## Thread Size:

0.190 inches

### Heat Treatment:

T-6 solution heat treated

#### Material:

Aluminum alloy 7075

#### **Material Specification:**

Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

## **Thread Series Designator:**

Unjf

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A528u0



# NSN 5320-00-972-3359

Pin-rivet - Page 2 of 2

## Mil-std (military Standard):

Mil-a-8625 spec.

