NSN 5320-00-972-3383

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-972-3383 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.135 inches and 1.155 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.755 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees Material: Steel comp 431 **Material Specification:** Ams 5628 assn standard single material response or mil-s-18732 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification all treatment responses **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-00-972-3383

Pin-rivet - Page 2 of 2



Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.