NSN 5320-00-972-3394

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-00-972-3394 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.347 inches and 1.367 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5554 inches and 0.5604 inches Lubrication: Cetyl alcohol **Grip Length:** 0.817 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Collar Style:** Straight type Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response or ams 5628 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5320-00-972-3394

Pin-rivet - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-18732 spec.