## NSN 5320-00-973-0686

Blind Rivet - Page 1 of 1

Fiig: A040a0

Mil-std (military Standard):

Mil-s-5002 spec.



View Online at https://aerobasegroup.com/nsn/5320-00-973-0686 **Head Style:** Hexagon **Head Height:** 0.096 inches **Shank Diameter:** Between 0.1625 inches and 0.1645 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem Lubrication: Wax or cetyl alcohol **Grip Length:** Between 0.094 inches and 0.156 inches Width Across Flats: Between 0.244 inches and 0.250 inches Material: Iron alloy 660 boltiron alloy 660 nutiron alloy 660 sleeve **Material Specification:** Ams 5735 assn standard single material response bolt or ams 5737 assn standard single material response boltams 5735 assn standard single material response nut or ams 5737 assn standard single material response nutams 5735 assn standard single material response sleeve or ams 5737 assn standard single material response sleeve **Surface Treatment:** Passivate boltpassivate nutpassivate sleeve **Surface Treatment Specification:** Mil-s-5002 military specification single treatment response boltmil-s-5002 military specification single treatment response nutmil-s-5002 military specification single treatment response sleeve Shelf Life: N/a **Unit Of Measure: Demilitarization:** No